

Compuprint 6214



The Compuprint 6214 offers itself as a reliable servant for those all who print smaller quantities of labels for direct use. Therefore you find it usually besides the user's PC to which it is connected directly by USB or to a server by Ethernet. With the network solution several users in a room, for example, have access to one Compuprint 6214.

The included software solution **CPLabel** is comprehensive and can be used without any limitations. It brings the user in a position to define off the cuff own labels and to print directly from Excel-sheets and data bases.

Useful add-ons like the solid cutter, the label dispenser, and the external label unwinder combined with a maximum speed of up to 7 inch per second make the Compuprint 6214 to a faithful companion even for challenging tasks – to a moderate price.

Value and Features

- quick desktop printer: up to 7 inch/sec
- compact even with added cutter
- team player thanks to Ethernet
- USB-Host-interface allows connection of keyboard or bluetooth scanner
- supports Unicode UTF8 & UTF16
- autocalibration at the touch of a button
- easy to use out of the box label designer



High Connectivity:

- + USB 2.0
- + seriell RS232
- + Ethernet 10/100 Base-T
- + USB-Host



The Control Centre:

The colour screen and the corresponding control elements including the on/off power switch.



Compuprint

Printing and Scanning Solutions

Compuprint 6214 – Your compact and useful companion in terms of label printing

Printer Model	PRT6214	PRT6214-H
Print Technology		Thermal Transfer & Direct Thermal
Resolution	203 dpi (8 dots/mm)	300 dpi (12 dots/mm)
Print Speed	up to 7 inch/second (177 mm/s)	up to 5 inch/second (127 mm/s)
Print Width	max. 108 mm	max. 105,7 mm
Print Length	4 mm – 1727 mm	4 mm – 762 mm
General Specifications		
Memory	Flash: 8 MB (4 MB for user storage)	SDRAM: 16 MB
Media Sensors	fixed reflective sensor (aligned in the middle) and adjustable transmissive sensor	
Interfaces - Standard	Rear: 1 USB-Host (A-Type) / USB 2.0 (B-Type) / serial RS-232 (DB-9) / Ethernet 10/100 Base-Tx IEEE 802.3 (RJ-45)	
Control Panel	LCD: Width: 50 mm, Height: 70 mm; several control elements including power switch	
Printer Language	CEL , CZL auto switch - (CEL: Compuprint Eltron Language; CZL: Compuprint Zebra Language)	
Driver	Windows XP – Windows 8.1 (32 & 64 bit), Server 2003 / 2008 / 2012	
Software	Label Design Software <i>CLabel</i>	
User Manual	PDF-File, English	
Graphical Data	Resident graphical file types: BMP & PCX; With CLabel further graphical formats are downloadable	
Fonts	Bitmap-Fonts Nr. 6,8,10,12,14,18,24,30 and OCR A & B; up to 8x expandable in horizontal & vert. directions	
1D-Codes (Barcodes)	Codabar, Code 39, Code 93, EAN 8, EAN 13, UPC A, UPC E, UPC and EAN 2 or 5 digit extensions, Interleaved 2 of 5 without and with Shipping Bearer Bars (ITF-14) Code 128 (Subset A, B, C), EAN 128, RPS 128, UCC 128, UCC / EAN-128 K-Mart, Random Weight, Post NET, ITF 14, China Postal Code, HIBC, MSI, Plessey, Telepen, FIM, GS1 DataBar	
2D-Codes	PDF417, Micro PDF417, Datamatrix, Maxicode, QR, Micro QR, Aztec	
Character Sets	Codepage 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 Windows Codepage 1250, 1251, 1252, 1253, 1254, 1255, 1257, Unicode: UTF8 & UTF16	
Real Time Clock	Standard	
Power Supply	external universal power supply, 100 – 240 V AC, 50 - 60 Hz	
Safety Approvals	CE (EMC), FCC Class A, CB, cUL, CCC	
Dimensions / Weight	Depth: 28,0 cm, Width: 21,0 cm, Height: 18,6 cm / 3 kg	
MTBF	15.000 h @ 5.000 labels/day	

Media and Consumables

Media Type	Continuous form, gap labels, black mark sensing, and punched hole; label length set by auto sensing or programming		
Media Width	Tear: 25,4 – 118 mm (1.0" - 4.64")		
Media Thickness	0,06 – 0,2 mm (0.003 – 0.01")		
Label Roll Diameter	max. 127 mm (5.0")	Core diameter	25,4 mm & 38,1 mm (1.0" – 1.5")
Ribbon Type	wax, wax/resin, resin – only inkside out		
Ribbon Width	30 – 110 mm (1.18" - 4.33")	Ribbon Length	max. 300 m (981")
Ribbon Roll Diameter	68 mm (2.67")	Core Diameter	25,4 mm (1.0")
Printhead	Flathead, durability up to 50 km		

Options

Cutter Module	6214-MCF
Label Stripper	6214-STR
External label Unwinder	6214-EXL

Compuprint

Melibokusstr. 18 68519 Viernheim GERMANY Tel. +49 6204 305640-0 info@compuprint.de www.compuprint.de	Via Cottolengo 77 10072 Caselle T.se (To) ITALY International:+39 011-9892-133 sales@compuprint.com www.compuprint.com
---	---

Consumables

6214 Printhead, 200 DPI, 7 IPS	6214-PH
6214-H Printhead, 300 DPI, 5 IPS	6214H-PH
Ribbon wax/resin (width: 108 mm, length: 300 m)	PRK6214



Copyright © 2016 Compuprint

The information contained in this document are subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners. Version 2, 15.2.2016