

UNI-FLEX Model Number	Conveyor Width	Standard Length Compacted - Expanded	Leg Sets per Unit	Rollers per Axle	Load Capacity per linear metre	Approx. Shipping Weight
UFP/ROS/0450/03.75	450 mm	1,250 mm – 3,750 mm	4	1	150 kg	186 kg
UFP/ROS/0450/07.50	450 mm	2,500 mm – 7,500 mm	7	1	150 kg	360 kg
UFP/ROS/0450/11.25	450 mm	3,750 mm – 11,250 mm	10	1	150 kg	534 kg
UFP/ROS/0450/15.00	450 mm	5,000 mm – 15,000 mm	13	1	150 kg	708 kg
UFP/ROS/0450/17.50	450 mm	5,830 mm – 17,500 mm	15	1	150 kg	824 kg
UFP/ROS/0600/03.75	600 mm	1,250 mm – 3,750 mm	4	1	150 kg	202 kg
UFP/ROS/0600/07.50	600 mm	2,500 mm – 7,500 mm	7	1	150 kg	391 kg
UFP/ROS/0600/11.25	600 mm	3,750 mm – 11,250 mm	10	1	150 kg	580 kg
UFP/ROS/0600/15.00	600 mm	5,000 mm – 15,000 mm	13	1	150 kg	769 kg
UFP/ROS/0600/17.50	600 mm	5,830 mm – 17,500 mm	15	1	150 kg	895 kg
UFP/ROS/0750/03.75	750 mm	1,250 mm – 3,750 mm	4	1	150 kg	218 kg
UFP/ROS/0750/07.50	750 mm	2,500 mm – 7,500 mm	7	1	150 kg	422 kg
UFP/ROS/0750/11.25	750 mm	3,750 mm – 11,250 mm	10	1	150 kg	626 kg
UFP/ROS/0750/15.00	750 mm	5,000 mm – 15,000 mm	13	1	150 kg	830 kg
UFP/ROS/0750/17.50	750 mm	5,830 mm – 17,500 mm	15	1	150 kg	966 kg
UFP/ROS/0900/03.75	900 mm	1,250 mm – 3,750 mm	4	1	150 kg	234 kg
UFP/ROS/0900/07.50	900 mm	2,500 mm – 7,500 mm	7	1	150 kg	453 kg
UFP/ROS/0900/11.25	900 mm	3,750 mm – 11,250 mm	10	1	150 kg	672 kg
UFP/ROS/0900/15.00	900 mm	5,000 mm – 15,000 mm	13	1	150 kg	891 kg
UFP/ROS/0900/17.50	900 mm	5,830 mm – 17,500 mm	15	1	150 kg	1,037 kg

Adjustable Height: The working height of UNI-FLEX Powered Roller Conveyors is infinitely adjustable from 770 mm to 1095 mm. If your application requires a specific height, please contact us for further assistance.

Axle Centre Distances: When expanded, the distance between axle centres is 125 mm. As an option, 75 mm and 100 mm axle centre distances are available. The optional axle centre distances affect the compacted conveyor length. Please contact us for further assistance.

Extended Lengths: UNI-FLEX Powered Roller Conveyors are available in any length. If your application requires a length that is not listed in the above chart, please contact us for further assistance.

