

LABEL mobile printer

BTP-P36 LABEL mobile printer



Features:

- High speed printing: 102mm/s
- Easily switch from receipt to label printing
- With LCD screen
- Long lasting battery life
- With peeler as standard for professional printing
- Support Bluetooth, Wi-Fi connection
- Ultra rugged with IP54, 1.5m drop reliability
- Compatible with major operating system including IOS®, Android®



Compatible with smart devices Water and dust resistance Peeler function

Applications:

- Mobile POS/Retail
- Customer Service Center
- Deliveries
- Ticketing

> BTP-P36 LABEL mobile printer

Item		BTP-P36
Print	Print method	Direct thermal line printing
	Resolution	203×203DPI
	Print width	Max. 72mm
	Print speed	Max.102mm/s
	Memory	RAM: 64MB , Flash: 16MB
	Interface	USB2.0+Bluetooth4.0; USB2.0+WIFI
Paper	Paper type	Continuous paper, Perforated paper, Marked paper, Label paper, liner-less paper(Optional)
	Paper thickness	0.06-0.16mm
	Paper roll OD	Max.67mm
	Paper roll width	25.4-80mm
	Paper cut	Tear off, Peel off
Barcodes Fonts Graphics	Barcodes	1D: UPC-A, UPC-E, JAN13 (EAN13), JAN 8 (EAN8), CODE39, ITF, CODABAR, CODE93, CODE128, UPC/EAN Extensions, Planet Code, Standard 2 of 5, Industrial 2 of 5, Interleaved 2 of 5, LOGMARS, GS1 DataBar(RSS), RSS-14, UCC/EAN 128 2D: PDF417, QR CODE, MAXICODE, GS1, MicroPDF417
	Fonts	Standard Font A(12X24), Font B (9X17), User defined character, Kanji (24×24), support Chinese (2312) , English (ASCII) , Support Simplified Chinese (18030 or GBK) , Traditional Chinese, America, English, Japanese, Korean (Option) , can download defined character to FLASH or RAM.
Operation	Display	LCD screen
	Alarm	Buzzer
	Battery capacity	7.4V Li-ion, 2600mAh, rechargeable
Power supply	Charging time	3.5 hours
	Input	100-240V AC, 50 ~ 60Hz
Protection	Output	12±5%V DC , 2A
	Spill and dust proof	IP54(with Nylon soft case)
Reliability	Drop test	1.5m
	TPH	50km
Physics Spec.	Dimensions	186.5(L) ×117(W)×81.5(H) mm
	Weight	638g (With battery)
Standards	Standards	CE, CB, FCC, UL