



PROFESSIONAL

GOLF 275 HV



Lifejacket level 275

www.secumar.com



GOLF 275 HV

The fireman's lifejacket – available with a tough polyamide or an aluminium coated NOMEX® outer cover for withstanding heat and sparks.

Developed specifically for the Fire Brigade and can be used with or without self-contained breathing apparatus. The arrangement of the harness straps enable the lifejacket to be worn over or under the compressed air cylinder, so the SCBA doesn't need to be removed to don the lifejacket. The special design of the buoyancy chamber provides enough space at the back of the neck to prevent the helmet being forced forward.

A D-ring at the back allows the connection to a safety line. For "hot" missions close to the fire the outer protective cover of aluminized NOMEX preserves the lifejacket from damage by heat and sparks.



SPECIFICATION

General technical data	
Type:	GOLF 275 HV
Part No.:	13996 (aluminium coated)
Approval:	EN ISO 12402-2
Buoyancy:	approx. 280 N
Colour:	Shining silvery
Weight:	approx. 1.5 kg
CO ₂ -Cartridge:	56 g CO ₂ -Cartridge
Size:	50 kg and more body weight up to 135 cm chest measurement
Temperature range:	Storage: -54 °C to +70 °C Operation: -10 °C to +70 °C
Geographical range:	unlimited*
Application:	Inflatable commercial lifejacket for fire brigades. Can be worn with or without breathing apparatus.

* to protect the SECUMAR Pill/Pill-Box against premature disintegration caused by high atmospheric humidity/temperature SECUMAR highly recommends to adapt the changing interval to these specific areas. The standard interval should be shortened to an appropriate period.

Protective Stole			
Integrated Safety Harness acc. to EN ISO 12401:	–	Colour:	Aluminized reflective
Material:	NOMEX®, aluminized	Closed with:	Velcro tape
Adjustment waist belt:	2 lateral sliders	Buckle:	SECUMAR Click-Buckle, 50 mm
Lifting becket (3,2 kN):	•	Back strap:	Double
Window:	–	Pocket for accessories:	–
Service-Zipper:	–	Pocket for nametag:	–

Characteristics:
 With the patented SECUMAR CLICK-buckle the donning and doffing of the lifejacket is very easy, it is donned like a normal jacket.
 The lifejacket SECUMAR GOLF 275 HV is designed for use with and without compressed air breathing apparatus. For this the double back straps are placed lateral to the compressed air cylinder.
 A D-ring in the neck part section allows safeguarding with a rope e.g. (N.B.: not a safety harness acc. to EN ISO 12401 or fall-arrest harness acc. to EN 363)

Buoyancy chamber			
Design:	Standard	Colour:	Orange
Oral valve:	•	Retro reflecting tape:	400 cm ² (Material: 3M®)
Material:	Polyurethane-coated polyamide fabric	Overpressure valve:	–
Pocket for transmitter:	–		

Characteristics:
 The neck part section of the buoyancy chamber is particularly flat designed. Even freedom of movement is not restricted if a helmet is worn.

- Standard/◦ Optional/– Not available

Inflation device

Operation:	Automatic activation upon the SECUMAR Pill contact with water.
Type:	SECUMATIC 3001S, Firefighter version
Indicator:	3 Indicators
Characteristics:	Torque safe tying system (Positorque®) prevents from unintended loosening of the CO ₂ -cartridge by means of vibration and shock. Three indicators offer an easy possibility of control and inspection before every use: SECUMAR Pill is inserted, CO ₂ -cartridge is fitted correctly and activation lever is secured.

Equipment

Sprayhood:	–	Crutch strap:	o
Distress light:	–	CO ₂ -Cartridge:	56 g CO ₂ -Cartridge
Neck fleece:	–	Buddy Line:	–
Transmitter:	–	Signal whistle:	•
Lifeline:	–	Instructions, multi-language:	•

Characteristics:

The service label on the waist belt shows you at a glance when your lifejacket should be serviced again by the SECUMAR service.

Model variants



Golf 275 HV
(blue, P/N: 14010)

with blue protective cover made of tear resistant Nylon® fabric

Optional Equipment/ Spare parts



56 g CO₂-Cartridge AUTO
(P/N: 929)



Distress light SECULUX CFX-II
(P/N: 12947)



Crutch strap 2K Click 30
(P/N: 14693)

• Standard/o Optional/– Not available

02/2015



CE: PPE in conformance with Directive 89/686/EWG, type-approved to EN standards and/or DIN EN ISO 12402



SECUMAR is a member of the Emergency Sea Rescue Equipment Trade Federation (FSR), a union of suppliers and importers of all water rescue equipment. For further information, see www.fsr.de.



Bernhardt Apparatebau GmbH u. Co.
Lifesaving Equipment for Sea and Air
PO Box 1190 · 25487 Holm, Germany
Tel.: +49 4103 125 – 0
Fax: +49 4103 125 – 100
www.secumar.com

