

ProVenger™ Nozzles & Foam Tubes

STYLES 1602, 1616, 1615, 4102, 4116, 4115, 624 & 638

The patent pending ProVenger family of 1" (25 mm) and 1 1/2" (38 mm) handline nozzles combine years of design and manufacturing experience with superior stream performance and dependability; all at an unbeatable value.

The ProVenger FG (fixed gallonage) nozzles offer a variety of pressures with the simplicity of a fixed orifice. The simple, rugged design is smooth to operate delivering a constant flow, hard-hitting straight stream. The ProVenger SG (selectable gallonage) nozzles are optimized from fog to straight stream with various flow settings for frontline flow control. The ProVenger SG's design gives the nozzleman flexibility to change the flow and reach depending on the situation.

Low flow options, starting at 5 gpm (19 lpm) are available within the 1" (25 mm) ProVenger line. Perfect for wildland and gas cooling applications.

- Lightweight fog and straight stream nozzle with multiple fixed or constant gallonage settings
- Raised indicator lug on the bumper for easy pattern identification
- Quickly adjust from straight stream to full fog with only a quarter-turn rotation
- Integrated control ring allows you to flush the nozzle without shutting down
- Meets NFPA 1964
- Meets European Standard EN 15182-2: 2007



STYLE 1616



Style 624 and 638 ProVenger Quick-Attack foam tubes are designed to efficiently snap-on and off the ProVenger handline nozzles using the unique, quick-release tabs. No tools are required. Constructed of lightweight, durable polymer the foam tubes provide air-aspirated foam with expansion ratios up to 12:1 with AFFF. The foam tube accessories are affordably priced to compliment the ProVenger nozzle series.



STYLE 624

STYLE 638

ProVenger™ Nozzles

Style	Gallonage	Pistol Grip	Swivel Inlet	Length	Weight lbs. (kg)	Flow Setting*		Max Operating Pressure
						GPM	LPM	
1602	Selectable	YES	1" (25.4 mm)	9 1/4" (235 mm)	3 (1.4 kg)	5-10-20-40 @ 75 or 100 psi 12-23-34-53 @ 86 psi	19-40-75-150 @ 5 or 7 bar 45-85-130-200 @ 6 bar	230 psi (16 bar)
4102	Fixed	YES	1" (25.4 mm)	9 1/4" (235 mm)	3 (1.4 kg)	5-10-20-40 @ 75, 86 or 100 psi	19-40-75-150 @ 5, 6 or 7 bar	230 psi (16 bar)
1616	Selectable	YES	1 1/2" or 2 1/2" (38 or 65 mm)	10 1/2" (267 mm)	4.3 (2 kg)	30-60-95-125-150	115-230-360-475-550	230 psi (16 bar)
1615	Selectable	-	1 1/2" or 2 1/2" (38 or 65 mm)	10 1/2" (267 mm)	4.3 (2 kg)	30-60-95-125-150	115-230-360-475-550	230 psi (16 bar)
4116	Fixed	YES	1 1/2" or 2 1/2" (38 or 65 mm)	10 1/2" (267 mm)	4 (1.8 kg)	60-95-125-150 @ 75, 86 or 100psi	230-360-475-550 @ 5, 6, or 7 bar	230 psi (16 bar)
4115	Fixed	-	1 1/2" or 2 1/2" (38 or 65 mm)	10 1/2" (267 mm)	4 (1.8 kg)	60-95-125-150 @ 75, 86 or 100psi	230-360-475-550 @ 5, 6, or 7 bar	230 psi (16 bar)

* Must specify when ordering

ProVenger Quick-Attack™ Foam Tubes

Style	Swivel Inlet	Length	Width	Weight lbs. (kg)
624	1" (25.4 mm)	12 3/4" (324 mm)	3 5/8" (92 mm)	0.9 (0.4 kg)
638	1 1/2" (38 mm)	18 5/8" (473 mm)	4 1/2" (114 mm)	1.8 (0.8 kg)