


UV - Flame Detector Type FL 80/1A



98802-88



G 28425

Characteristic:

- Housing Aluminum
- Type of Protection IP65
- Optical Location Angle 180°
- Use for every Fire Alarm Control Panel
- Certificate: Verband der Sachversicherer (VdS)
- Certificate: MED, Germanischer Lloyd (GL)

Technical Data:

Measurement	: 110x120x155 mm
Weight	: 1,4 kg
Fire Detect	: EN 54-10 Class 1
Power Supply	: 24V DC
Ambient Temperature	: -20°C until +80°C
Outputs	: Potential-free change over contact

All rights strictly reserved, except when stipulated otherwise expressly by contract. Reproduction or issue to third parties in any form whatsoever is not permitted without written authority from the proprietors.

Alle Rechte, soweit nicht vertraglich anders vereinbart, sind ausdrücklich vorbehalten. Vervielfältigung oder Mitteilung an Dritte, gleichgültig in welcher Form, ist ohne schriftliche Genehmigung des Eigentümers nicht gestattet.

Datum/Date 30.05.12

Version 4

EGON HARIG GmbH
Gewerbering 4 * D-22113 Oststeinbek
Tel./Phone: +49 (0)40 713752-0
Telefax: +49 (0)40 713752-24
E-Mail: egonharig@egonharig.de
www.egonharig.de www.flamtron.de

Prospektblatt Nr./Pamphlet sheet No

S-PB-4.9194-1

Seite/Page 1 von/of 1