

Product Description

Brand Name: Orientx Fire

External epoxy paint adds extra protection to with stand extreme temperature

Product Description: Sticker label or screen printing

Valve with CE approval to ensure reliability and optimizes efficiency

23mm series of diaphragm pressure gauge with EN3 approval

Listed extinguisher can be with wall bracket/plastic bottom case/special specification bracket to choice available

Listed cylinder with European Directive PED97/23/EC with CE mark

1KG 40% ABC POWDER DNV EN3 APPROVAL EXTINGUISHER

• Product Code / 产品代码:	MFZL1EN- I
• Shell-Approx(mm) / 钢瓶直径:	85
• High-Approx(mm) / 钢瓶高度:	270
• Capacity(L) / 灭火器容积:	1.25
• Filling Charge / 药剂名称:	40%ABC
• Weight Full-Approx(kg) / 整机重量:	2.2
• Discharge Time-Approx(S)Min / 喷射时间:	≥6s
• Test Pressure(bar) / 测试压力:	27
• Working Pressure(bar) / 工作压力:	14
• Temperature Range / 工作温度:	-30°C ~ +60°C
• Fire Rating / 灭火等级:	5A 34B
• Packing Specification-Complete(mm) / 装箱尺寸	
1pcs / box(1具/箱):	115*90*345
10pcs / box(10具/箱):	485*250*365



Certified to DNV EN3

Pressure Equipment Directive Approved Fire Extinguisher

ISO9001 Certified Quality System by BSI



2KG 40% ABC POWDER DNV EN3 APPROVAL EXTINGUISHER

• Product Code / 产品代码:	MFZL2EN- I
• Shell-Approx(mm) / 钢瓶直径:	110
• High-Approx(mm) / 钢瓶高度:	317
• Capacity(L) / 灭火器容积:	2.5
• Filling Charge / 药剂名称:	40%ABC
• Weight Full-Approx(kg) / 整机重量:	4
• Discharge Time-Approx(S)Min / 喷射时间:	≥9s
• Test Pressure(bar) / 测试压力:	27
• Working Pressure(bar) / 工作压力:	14
• Temperature Range / 工作温度:	-30°C ~ +60°C
• Fire Rating / 灭火等级:	13A 70B
• Packing Specification-Complete(mm) / 装箱尺寸	
1pcs / box(1具/箱):	135*115*390
6pcs / box(6具/箱):	360*285*410



Certified to DNV EN3

Pressure Equipment Directive Approved Fire Extinguisher

ISO9001 Certified Quality System by BSI