



TRAILER – OIL BOOM III

Product

Box trailer (tarpaulin / roof carline) with complete oil spill equipment for the mobile oil boom operation. Equipped with inflatable oil boom 250/350/600 L and complete set of accessories, optionally with rubber dinghy RTB1. Oil boom wound onto horizontal reel, set of accessories in storage and transport boxes, stored in aluminium section system rack.

Standard design, resp. according to customers' requests.



Technical data


Trailer:

One-axle trailer (tandem axle), approx. 4000 x 2200 x 1800 mm, 2.6 tons, reduced to 2.0 tons, vertically adjustable towing device, overrun brake with backup automatic system, hand brake lever supported by gas spring, spherical head/ DIN-coupling ring, axles made in maintenance-free quality as rubber-shock axles with individual wheel suspension and hexagonal axle body, with maintenance-free radial angular ball bearings (compact contact bearing), chassis as well as all fittings completely made of corrosion-protected quality according to EN 1846-2, carrying wheel at the front, 2 landing gears at the back, non-slid base plate, waterproof, oil-resistant, petrolproof (waterproof plywood plate, phenolic-resin coated), side boards to be hinged at 3 sides, made of anodized

Horlecke 34 – 38 · D-58706 Menden

Fon: +49 (0) 2373 770099-0 · Fax: +49 (0) 2373 770099-9

www.alles-optimal.de · info@alles-optimal.de



TRAILER – OIL BOOM III

Technical data

aluminium sections equipped with step, rack and roof carline corrosion-protected, made of hot-dip galvanized steel, planed wooden boards for insertion, internal height 1800 mm, tarpaulin to be rolled up at 3 sides, to be fixed to the side board by swivels, colour of tarpaulin red, 2 wheel chacks, wheel nut spanner, plug-in adapter, lighting according to EU regulation, operating voltage 12 V, backup lamps at both sides, lighting completely protected, 13-pin trailer plug socket, adapter 7-pin / 13-pin coupling.

Reel:

mechanical horizontal reel, \varnothing appr. 2000 mm, ball bearing slewing ring made of zinc-plated steel, base plate made of waterproof plywood, hand brake and transport locking mechanism, trip gear for oil boom in case of emergency.

Equipment:

maximum 200 metres oil boom wound onto horizontal reel, set of accessories (couplings, bank reinforcement, ropes, tools) in solid storage and transport boxes with marks of contents, 600 x 400 x 320 mm, stored in aluminium section system rack. The rubber dinghy which can be optionally mounted lies on the rack fixed by lashing straps.

A weathertight plan how to load the trailer is fixed to both side boards on the inside.



Operative range

This trailer is especially designed for quick first response. Equipped with oil boom and complete set of accessories, an application independent from other units is possible. The wound oil boom is ready for operation and can be towed directly into the water at the place of damage.

Horlecke 34 – 38 · D-58706 Menden

Fon: +49 (0) 2373 770099-0 · Fax: +49 (0) 2373 770099-9

www.alles-optimal.de · info@alles-optimal.de